

- Contains NS-54[™] nitrogen to provide uniform growth with extended nitrogen feeding
- Provides iron and manganese for improved turf color and turf vigor.

GUARANTEED ANALYSIS

Total Nitrogen (N)	17.00%
Available Phosphate (P ₂ O ₅)	3.00%
Soluble Potash (K ₂ O)	
Sulfur (S)	6.79%
0.99% Free Sulfur (S)	
5.80% Combined Sulfur (S)	
Iron (Fe)	3.00%
Manganese (Mn)	1.00%
0.14% Water Soluble Manganese (Mn)	

*10.68% slowly available nitrogen from polymer coated sulfur coated urea.

F292

Information regarding the contents and levels of metals in this product is available on the internet at http://www.regulatory-info-ap.com

DIRECTIONS FOR USE

Apply only as directed. Apply during the growing season.

Application Rates:

LOW RATE: 4.4 lbs/1,000 sq. ft. MEDIUM RATE: 5.8 lbs/1,000 sq. ft. HIGH RATE: 7.4 lbs/1,000 sq. ft.

FLORIDA APPLICATIONS: We recommend that you follow the Florida Green Industries BMP's at http://www.flaes.org/pdf/BMP_Book_final.pdf

FLORIDA APPLICATIONS: We recommend that you follow the Florida Golf Course BMP's at http://www.flaes.org/pdf/glfbmp07.pdf

For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to prevent particle pick-up.

Note: This product contains the micronutrient iron for extra greening and to help prevent iron deficiency. Iron may stain concrete and other surfaces. Misapplied product to these surfaces should be removed promptly by sweeping or blowing. DO NOT WASH OFF WITH WATER.

Recent research has shown that well-maintained turf is an effective environmental buffer that prevents pollutants from entering our natural water bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

STORAGE AND USE

Store in a clean, dry place. Reseal opened bag by folding top down and securing. Use only clean, dry spreaders. Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION

Product of U.S.A.

Manufactured by:
The Andersons Lawn Fertilizer Division, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonsgolfproducts.com

Andersons Golf Products is a registered trademark of The Andersons, Inc.; NS-54 is a trademark of The Andersons, Inc.

SUGGESTED SPREADER SETTINGS Suggested spreader settings are not intended to replace calibration. Please calibrate your spreader prior to applying product. 50 lbs. covers 11,300 sq. ft. (0.26 acre) with 0.75 lbs. N/1,000 sq. ft. at the LOW RATE 50 lbs. covers 8,600 sq. ft. (0.20 acre) with 0.99 lbs. N/1,000 sq. ft. at the MEDIUM RATE 50 lbs. covers 6,700 sq. ft. (0.15 acre) with 1.25 lbs. N/1,000 sq. ft. at the HIGH RATE						
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	LOW RATE 4.4 lbs/1,000 sq. ft.	MEDIUM RATE 5.8 lbs/1,000 sq. ft.	HIGH RATE 7.4 lbs/1,000 sq. ft.	
Andersons AccuPro 2000, SR-2000 (cone 3)	3 mph	12 feet	L 1/2	M 1/2	N 1/4	
Scotts Rotaries R-8, R-8A (cone 3)	3 mph	12 feet	J 1/2	K 1/2	M 1/2	
LESCO Model 020093 (pattern 0.25)	3 mph	8 feet	Н	l 1/2	К	
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern III-B	4.5 mph	40 feet	6	6 3/4	7 1/2	
Vicon (03 Series)	4.5 mph	35 feet	32	36	41	

SGN 215 Net Wt. 50 Lbs. (22.68 kg)



AGC171M5.1

J10* (AGCBLKPGRN.1B)